

TITAN[®] STANDING SEAM METAL ROOFING PANEL **CB-150**

ENERGY EFFICIENCY WITH STYLE & DURABILITY



METAL ROOFING FOR RESIDENTIAL AND COMMERCIAL APPLICATIONS.

(every Featuring the **TITAN® Cool Roof** Reflective Paint

CUSTOM-BILT METALS.

LAST-TIME[®] Brand Products Since 1974



STANDING SEAM PANEL ESED ASIME 1800, E-104b



COMPARE PANEL FEATURES

The adjacent chart allows you to compare the various features, options and benefits of different standing seam metal panel systems. Select the seam height, panel width, options, locking system, gauge and engineering suited best for your job.

CLASSIC STYLING

Standing Seam metal roofing is one of the oldest and most practical roofing solutions. It's classic look enhances the roofline of virtually all architecture styles. It produces dramatic shadow lines that run continuously from ridge to eave accenting the pitch and plane of every roof angle. Panels may be roll formed at your jobsite or in our factories.

LAST-TIME DURABILITY.

The CB-150 is available in 25 colors featuring TITAN® COOL ROOF Reflective paint system. This system offers an incredible 35 year no fade warranty.

TITAN[®] COOL ROOF

Our reflective paint features BASF® and KYNAR[®] 500 reflective pigmentation technology to deliver highly efficient cooling performance. Testing data supports reflectivity of up to 60% of the heat from the sun and energy savings of up to 20%. Now you can have darker roof colors and still enjoy energy savings.


For complete guide specifications and installation details, visit our website.

www.custombiltmetals.com

CUSTOM-BILT METALS.

LAST-TIME® Brand Products Since 1974

CUSTOM-B METALS	ILT	Sean Height	Ponel Widths	nimum Slope	red Panel OF	in Sector	phon tothes work tothes int sport	onthe Application Application	IED UL 580-C	DIED ASTM
		Seon Standar	, Mi	nime Cur	led 1 Sec	Im Section Weath	er hyaliat AVAILAT Spor	sed PD RA	IED UT TH	STED ASTME
CB-2000 Mechanical Seam	2 inch	14", 18"	¹ / ₂ " in 12"							
CB-150 Mechanical Seam	1 1/2″	12″, 16″	1″ in 12″							
CB-100 Mechanical Seam	1 inch	13″, 17″	1″ in 12″	0	0	0	0	0	0	0
SL-1750 Snap Lock	1 3/4″	14", 18"	3″ in 12″	0						
SL-100 Snap Lock	1 inch	12″, 16″	3″ in 12″	0	0	0	0	0		0
SLZ-1000 Snap Lock	1 inch	13″, 17″	3″ in 12″	0	0	0	0	0		0
CS-100 Cap Seam	1 inch	141/2", 181/2"	3″ in 12″		0	0	0		0	
WS-100 Wall & Soffit	1 inch	12″	NA	0	0	0		NA	NA	0
oduct availability va	ries in each			1			1		• YE	S O NO



12" & 16" **CB-150**

$1 \frac{1}{2}$ " HIGH TITAN CB-150 MECHANICAL SEAM Allowable Live Load (psf)													
	# of equal	Panel Span (ft.)											
	Span	2	3	4	5								
12″ width	1	235	104	59	38								
24 Gauge	2	239	106	60	38								
	3	279	124	70	45								
16″ width	1	144	64	36	23								
24 Gauge	2	144	64	36	23								
	3	168	75	42	27								

Loads shown are limited by L/240 deflection

CUSTOM-BILT METALS LOCATIONS

Kent, WA (253) 872-7330 Chino, CA W. Sacramento, CA (916) 372-3706 Portland, OR (503) 256-3328

Phoenix, AZ (602) 484-7015 Hayward, CA (800) 537-6040 Spokane, WA Honolulu, HI (808) 845-1806

New Orleans, LA (504) 838-9344 San Jose, CA (800) 537-6040 Emporia, KS Mesquite, TX (214) 664-4161

Last-Time® and TITAN® are a registered trademarks of Custom Bilt Metals. Kynar 500® is registered to ATOFINA Chemicals; Ultra Cool® is registered to BASF Corporation; and Zincalume® is registered to BIEC International.

© 2006 Custom Bilt Metals, all rights reserved. Printed in the USA 0706-20M.

MATERIALS:

Prefinished or Bare Zincalume/Galvalume or G-90 Galvanized Steel in 24 & 26 gauge, 22 gauge (non-standard) Copper-16oz. or 20oz.(non-standard) Prefinished Aluminum in .032 Thickness

PAINT AND COLOR:

Titan Cool Roof Reflective Paint utilizing BASF and Kynar 500 technology in 25 colors. See architectural color selection chart, and request an actual metal sample for final paint and color selection.

SPECIFICATIONS:

Mechanical seam locking standing seams $1 \frac{1}{2}$ high with a panel width of 12 or 16" (Other widths available as non-standard)

RECOMMENED OPTIONS:

Stiffening ribs or striations





CALL 1-800-826-7813 for the closest sales representative. To contact our Corporate Office in Chino, CA Call: (909) 664-1500